

KVR/B

High performance ROOF fan

- The energy saving, versatile and cost-efficient fan
- High quality metal housing with corrosion resistant powder coating
- Reliable, established and proven design
- Roof installation
- For mounting, we recommend using cushioned clamps to reduce noise transmission into the ducting system
- Voltage-controlled air flow rate adjustment
- Built-in thermostatic switch with automatic reset
- Maintenance-free and quiet in operation
- Horizontal air release
- Galvanized steel case
- Insulation Class Motor: F
- IP Complete Unit: IP44



Model	U _N V	f _N Hz	SP. Pa	P _N W	v cfm / m ³ /h	N rpm	Insulation class	Protection class	T °C	Noise (dB)	W*L*H mm
A KVR/B 192	220-240V ~ 50	50	330	62	330 / 560	2500	F	IP44	60	62	370*370*179
B KVR/B 220	220-240V ~ 50	50	420	105	490 / 835	2500	F	IP44	60	67	370*370*170
C KVR/B 225	220-240V ~ 50	50	600	130	650 / 1100	2500	F	IP44	60	70	370*370*209
D KVR/B 250	220-240V ~ 50	50	550	160	750 / 1280	2500	F	IP44	60	72	370*370*220
E KVR/B 280	220-240V ~ 50	50	780	220	910 / 1550	2500	F	IP44	60	74	450*450*220
F KVR/B 315	220-240V ~ 50	50	300	130	1175 / 2000	1400	F	IP44	60	63	450*450*280

